VAL TEX

SAFETY DATA SHEET

1. Identification

A CMC MATERIALS COMPANY

Product identifier Val-Tex 972, Val-Tex 972-S

Other means of identification

Synonyms Includes sticks of all sizes and bulk packaging.

Recommended use Valve lubricant and sealant

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer/Supplier CMC Materials; 15431 Vantage Pkwy E. Suite 210; Houston, Texas 77032; United States

Telephone 1.800.627.9771

E-mail sales.val-tex@cmcmaterials.com

Representative CMC Materials; Amber Business Centre; Riddings Alfreton Derbyshire DE55 4DA; United

Kingdom

Telephone +44 (0) 1773 844200

E-mail sales.val-tex@cmcmaterials.com

Representative CMC Materials; Les Vieilles Hayes; 50620 Saint Fromond; France

Telephone +33 (0) 2 33 75 64 00

E-mail sales.val-tex@cmcmaterials.com

Distributor CMC Materials Sealweld Canada, INC.; Bay 106, 4116 64th Ave.S.E., Calgary, AB, T2C 2B3

Telephone 1.800.661.8465

E-mail sales.val-tex@cmcmaterials.com

Emergency phone number

3E Global Incident Response Hotline

> USA +1.866.519.4752 International +1.760.476.3962

Access code 333035

CHEMTREC For Dangerous Goods Incidents ONLY (spill, leak, fire, exposure or accident), call

CHEMTREC 24/7 at:

Canada, USA +1.800.424.9300 **International** +1.703.741.5970

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Not classified.

OSHA defined hazards Not classified.

Label elements

Hazard symbol None.
Signal word None.

Hazard statement The mixture does not meet the criteria for classification.

Precautionary statement

Prevention Observe good industrial hygiene practices.

Response Wash hands after handling.

Val-Tex 972, Val-Tex 972-S
SDS US

Store away from incompatible materials. **Storage**

Dispose of waste and residues in accordance with local authority requirements. **Disposal**

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information After prolonged contact with highly porous materials, this product may spontaneously combust.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Amorphous Silica	112945-52-5	8.5
Molybdenum disulfide	1317-33-5	1.8

Composition comments All concentrations are in percent by weight unless otherwise indicated.

Components not listed are either non-hazardous or are below reportable limits.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Rinse with water. Get medical attention if irritation develops and persists. Eve contact

Rinse mouth. Get medical attention if symptoms occur. Ingestion Most important Direct contact with eyes may cause temporary irritation.

symptoms/effects, acute and delayed

Treat symptomatically.

Indication of immediate medical attention and special treatment needed

General information

Remove and isolate contaminated clothing and shoes. Clothing contaminated with this product may spontaneously catch fire if improperly discarded. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Specific hazards arising from the chemical

Special protective equipment

and precautions for firefighters Fire fighting

equipment/instructions

Specific methods

General fire hazards

wetted with this material. During fire, gases hazardous to health may be formed. Combustion products may include: carbon oxides, metal oxide, silicon oxides, sulfur oxides. Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Porous material such as rags, paper, insulation, or organic clay may spontaneously combust when

Do not point solid water stream directly into burning oil to avoid spreading. Water may be

ineffective in fighting an oil fire unless used by experienced firefighters. Use standard firefighting procedures and consider the hazards of other involved materials.

Will burn if involved in a fire. Spontaneous combustion can occur.

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up The product is immiscible with water and will sediment in water systems. Stop the flow of material, if this is without risk. Contain the discharged material. Shovel the material into waste container. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS. Clean contaminated area with oil-removing material. Rags, steel wool, or waste contaminated with this product may spontaneously catch fire if improperly discarded. Used rags or other cleaning materials should be soaked with water and placed in a sealed container.

Environmental precautions Avoid discharge into drains, water courses or onto the ground.

Val-Tex 972, Val-Tex 972-S SDS US

7. Handling and storage

Precautions for safe handling Porous material such as rags, paper, insulation, or organic clay may spontaneously combust when

wetted with this material. May auto-oxidize with sufficient heat generation to ignite if spread (as a thin film) or absorbed on porous or fibrous material. Contaminated rags and cloths must be put in

fireproof containers for disposal. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store in tightly closed container. Store away from incompatible materials (see Section 10 of the

SDS).

8. Exposure controls/personal protection

Occupational exposure limits

Components	Туре	Value	Form
Molybdenum disulfide (CAS 1317-33-5)	PEL	15 mg/m3	Total dust.
US. OSHA Table Z-3 (29 CFR 1910.	1000)		
Components	Туре	Value	
Amorphous Silica (CAS 112945-52-5)	TWA	0.8 mg/m3	
		20 mppcf	
US. ACGIH Threshold Limit Values	3		
Components	Туре	Value	Form
Molybdenum disulfide (CAS 1317-33-5)	TWA	3 mg/m3	Respirable fraction.
		10 mg/m3	Inhalable fraction.
US. NIOSH: Pocket Guide to Chem	ical Hazards		
Components	Type	Value	

Amorphous Silica (CAS TWA 6 mg/m3

112945-52-5)

Biological limit valuesNo biological exposure limits noted for the ingredient(s).

Exposure guidelines
Appropriate engineering

Occupational Exposure Limits are not relevant to the current physical form of the product.

Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been

established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Skin protection

Other Wear suitable protective clothing.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective

equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical stateSolid.FormSemi-solid.ColorBlack.

Odor Slight castor oil smell.

Odor threshold Property has not been measured.

pH Property has not been measured.

Val-Tex 972, Val-Tex 972-S SDS US

Melting point/freezing point Property has not been measured. Initial boiling point and boiling Property has not been measured.

range

500 °F (260 °C) Cleveland Open Cup Flash point **Evaporation rate** Property has not been measured. Flammability (solid, gas) Will burn if involved in a fire.

Upper/lower flammability or explosive limits

Explosive limit - lower (%) Property has not been measured. Explosive limit - upper (%) Property has not been measured. Vapor pressure Property has not been measured. Vapor density Property has not been measured. 1.0135 - 1.2976 (H2O=1)

Relative density

Solubility(ies)

Solubility (water) Insoluble in water.

Partition coefficient Property has not been measured.

(n-octanol/water)

Auto-ignition temperature Property has not been measured. **Decomposition temperature** Property has not been measured. **Viscosity** Property has not been measured.

Other information

Density Property has not been measured. > 500 °F (> 260 °C) ASTM D-566 **Dropping point**

Explosive properties Not explosive.

Kinematic viscosity Property has not been measured.

Oxidizing properties Not oxidizing.

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Porous material such as rags, paper, insulation, or organic clay may spontaneously combust when

Material is stable under normal conditions. Chemical stability

Possibility of hazardous

Hazardous decomposition

reactions Conditions to avoid

wetted with this material. Contact with incompatible materials.

Incompatible materials Strong oxidizers.

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Vapor from heated material or mist may cause respiratory irritation.

Skin contact Prolonged skin contact may cause temporary irritation. Direct contact with eyes may cause temporary irritation. Eye contact

Ingestion May cause discomfort if swallowed.

Information on toxicological effects

Not expected to be acutely toxic. **Acute toxicity**

Components **Species Test Results**

Molybdenum disulfide (CAS 1317-33-5)

Acute Inhalation

LC50 Rat > 2820 mg/m3, 4 hours

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Val-Tex 972, Val-Tex 972-S SDS US Serious eye damage/eye

irritation

Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Amorphous Silica (CAS 112945-52-5) 3 Not classifiable as to carcinogenicity to humans.

NTP Report on Carcinogens

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazardDue to the physical form of the product it is not expected to be an aspiration hazard.

Further information The product contains a substance with endocrine disrupting properties.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available on bioaccumulation.

Mobility in soil The product is insoluble in water. Expected to have low mobility in soil.

Other adverse effects The product contains a substance with endocrine disrupting properties.

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site.

Porous combustible material contaminated with this product must be collected in a tightly closed metal container. Cover with water, or a solution of water and detergent. Store in a cool place.

Protect from heat and direct sunlight.

Local disposal regulationsDispose in accordance with all applicable regulations.

Hazardous waste codeThe waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose in accordance with local regulations. Dispose of in accordance with local regulations.

Empty containers or liners may retain some product residues. This material and its container must

be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78 and

the IBC Code

Val-Tex 972, Val-Tex 972-S SDS US

15. Regulatory information

US federal regulations

This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard

Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Toxic Substances Control Act (TSCA)

All components of the mixture on the TSCA 8(b) inventory are designated

"active".

Superfund Amendments and Reauthorization Act of 1986 (SARA)

No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Contains component(s) regulated under the Safe Drinking Water Act.

(SDWA)

US state regulations

US. Massachusetts RTK - Substance List

Amorphous Silica (CAS 112945-52-5) Molybdenum disulfide (CAS 1317-33-5)

US. New Jersey Worker and Community Right-to-Know Act

Not listed.

US. Pennsylvania Worker and Community Right-to-Know Law

Amorphous Silica (CAS 112945-52-5)

US. Rhode Island RTK

Not regulated.

California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes

Val-Tex 972, Val-Tex 972-S SDS US

Country(s) or region Inventory name On inventory (yes/no)*

Philippines Philippine Inventory of Chemicals and Chemical Substances Ye

(PICCS)

Taiwan Taiwan Chemical Substance Inventory (TCSI)

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date18-March-2016Revision date06-August-2021

Version # 03

NFPA ratings



Disclaimer

CMC Materials Val-Tex cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.

Val-Tex 972, Val-Tex 972-S SDS US