

VALVE LUBE SEALANT SPECIFICATION SHEET

700+FTFE

SCOPE

Valve lube sealant specifications.

ORDERING OPTIONS

Val-Tex Part Number: 700+FTFE stick in B, C, D, G, J, K and V

700+FTFE-S bulk in P packs, 12 oz crtg, 10 lb. can, 40 lb. pail, 120 lb. drum, and 440 lb. drum

REQUIREMENTS

General

This synthetic, biodegradable lube sealant is suitable as a multi-purpose emergency lube sealant. It is resistant to natural gas, mineral oils, light hydrocarbons, LPG's, most aromatics, water, instrument air, H₂S, and CO₂. Moly-disulfide helps to reduce valve operating torque. It is designed as an emergency sealant containing blended particles of Polytetrafluoroethylene. Intermingling of Val-Tex 700+FTFE and other lubricants or sealants will not have an adverse affect. Please consult the factory with any specific questions.

Physical Characteristics

Worked Penetration at 77° F - ASTM D 217

Bulk: 138 typical

Stick: 70.5 typical

Dropping Point - ASTM D-566

Bulk: over 490° F typical

Stick: over 490° F typical

National Lubricating Grease Institute Consistency Number

Bulk: 5 typical

Stick: 6 typical

Temperature Range for Proper Lubrication

Bulk: -20° F to +450° F typical

Stick: -20° F to +450° F typical

Color - Black

REFERENCE STANDARDS AND SPECIFICATIONS

ASTM D 217 Cone Penetration of Lubricating Grease

ASTM D 566-64 Dropping Point of Lubricating Grease

BIODEGRADABLE VALVE FLUSH AND VALVE LUBE SEALANTS

EMAIL SALES.VAL-TEX@CMCMATERIALS.COM