

VALVE LUBE SEALANT SPECIFICATION SHEET

# SURE SEAL 1502

## SCOPE

Valve lube sealant specifications.

## ORDERING OPTIONS

Val-Tex Part Number: 1502-S bulk in 7 lb. can

## REQUIREMENTS

### General

This biodegradable grease is suitable for assembly of high pressure plug valves. It is for hand application only and not to be pumped. The unique viscosity and Sure Seal technology allows for consistent and even coverage of the plug and segments and helps ensure the valve seals at either low or high pressure. Val-Tex Sure Seal 1502 will seal a valve when it is tested at low pressure first, without the requirement of an initial high pressure test.

### Physical Characteristics

Worked Penetration at 77° F - ASTM D 217

Bulk: 241 typical

Dropping Point - ASTM D-566

Bulk: over 500° F typical

National Lubricating Grease Institute Consistency Number

Bulk: 3 typical

Temperature Range for Proper Lubrication

Bulk: -10° F to +400° F typical

Color - Amber

## REFERENCE STANDARDS AND SPECIFICATIONS

ASTM D 217 Cone Penetration of Lubricating Grease

ASTM D 566-64 Dropping Point of Lubricating Grease

**BIODEGRADABLE VALVE FLUSH  
AND VALVE LUBE SEALANTS**

**EMAIL** [SALES.VAL-TEX@CMCMATERIALS.COM](mailto:SALES.VAL-TEX@CMCMATERIALS.COM)