C1200

Contact your CR Wall Representative or call 519-624-9293 for more information

www.crwall.com | 519-624-9293 customerservice@crwall.com The model C1200 Hydraulic Squeeze Off Tool is designed to squeeze 8 " to 12 " MDPE and HDPE pipe safely and effectively.

> The C1200 features 8-sided, positive locking, indexable gauge plates, aircraft grade aluminum squeeze bars, chromeplated steel side shafts and a 10,000 PSI hydraulic system with quick connect fittings. This CNC machined tool contains no welded parts and exerts 150 tons of squeezing force.

> > The unique lock-in / swing-out bottom bar design allows forquick and easy access to the pipe, even in confined spaces, and the lock down bolts ensure that a squeeze is maintained even if the hydraulics are disconnected. The 00 also incorporates an efficient dog bone design on the jaws to obtain maximum flow control, while requiring minimal force to squeeze the pipe.

The C1200 also includes a standard grounding spike, and custom gauge plates are available upon request.

Standard Gauge Plate Settings 8" (SDR 9, 11, 11.5, 13.5) 10" (SDR 11, 11.5, 13.5, 15.5) 12" (SDR 9, 11, 11.5, 13.5, 15.5)

C1200-25



Air/Hydraulic pump kit,foot operated c/w controlled release valve,pressure gauge and 20' hoses. For model C1200-A2 & C36S-A1

> For 8" to 12" PE & HDPE Pipe 525lbs / Height 37" to 51" / Width 34" Pump Required: Model C1200-25 ASTM Approved