

F-19, F-4, F-5, F-31 Filter Dryer



The Welker F series Filter Dryer series helps protect sensitive instrumentation equipment from damage and contamination by cleaning and drying natural gas or instrument air for use as a pneumatic instrument supply.

With a variety of sizes, Welker has the Filter Dryer needed to meet the flow capacity and space requirements for your application.

FEATURES

- Spin on filter body
- Mounting bracket
- Filter cartridge media to remove water, liquid hydrocarbons, mercaptan, and sulfur

BENEFITS

- Simplified cartridge change outs
- Clean, dry supply gas

SPECIFICATIONS

F-19, F-4, F-5, F-31 Filter Dryer



	F-19	F-4	F-5	F-31
Materials of Construction	Carbon Steel			
	Others Available			
Seal Material	Buna			
	Others Available			
Operating Pressure	1500 psig @ -20 °F to 200 °F			
	Higher Pressures Available			
Connections	¼" FNPT			1" FNPT
Flow Rate	Up to 50 scfm			Up to 185 scfm
Nominal Filter Rating	3 Microns	0.45 Micron	1.2 Microns	0.45 Micron
		3 Microns	3 Microns	1.2 Microns
Options	Drain Valve	Drain Valve		Drain Valve
		Internal Bypass		
	External Bypass	Moisture Indicating Eye		External Bypass

Weight and/or dimensions are approximate. Specifications subject to change without notice.

