

VALVE INTEGRITY MADE EASY

# VALVE CARE PRODUCTS

## BUYER'S GUIDE



Sealweld® 

CANADA'S BEST MANAGED COMPANIES

ZEROMAX

### PINNACLE #200

#### PREMIUM SYNTHETIC WELLHEAD BODY FILLER

Sealweld® **Pinnacle #200** is a synthetic wellhead body filler lubricant that contains special additives to inhibit rust, corrosion and oxidation in side valve body cavities and reduce friction on moving parts. This product has excellent resistance to breakdown and washout in drilling fluids, sour gas and other typical drilling by-products.

Wellhead gate valves take the brunt of the punishment especially when abrasives like sand and rock contact sensitive sealing areas. The excellent adhesive properties of Sealweld® **Pinnacle #200** helps protect seat and stem seals from premature breakdown and washout by forming a barrier around these abrasive particles. These properties make **Pinnacle #200** suitable for hydraulic fracturing applications that produce very extreme operating conditions. Use **Pinnacle #200** in wellhead gate valves, stem seals, gearboxes and bearing assemblies.



Special Additives:	<b>Graphite</b>	ASTM Penetration:	<b>265-295</b>	Colour:	<b>Red</b>
Particle Size:	<b>Micronized</b>	Compatibility:	<b>Excellent</b>	Texture:	<b>Tacky</b>
Composition:	<b>Semi-liquid</b>	Solvent Resistance:	<b>Excellent</b>	Drop Point:	<b>&gt; 500°F/260°C</b>
Temp. Range:	<b>0°F to +400°F</b> <b>-18°C to +204°C</b>	Base Oil:	<b>Synthetic</b>	Specific Gravity:	<b>0.89</b>

**SAFE FOR ALL TYPES OF VALVES**

Available in: 11oz & 15oz cartridges as well as 10lbs & 40lbs pails. Contact us for bulk orders.

**SEALWELD CORPORATION**  
#106, 4116 – 64TH AVENUE S.E.  
CALGARY, ALBERTA,  
T2C 2B3 CANADA

**T** 403.236.0043 [24HRS]  
**F** 403.236.5487  
**TOLL FREE** 1.800.661.8465  
**E** CANSALES@SEALWELD.COM

**SEALWELD (USA) INC.**  
11430 BRITTMOORE PARK DRIVE  
HOUSTON, TX, U.S.A  
77041

**T** 713.466.7373  
**F** 713.466.7778  
**TOLL FREE** 1.800.624.4301  
**E** USASALES@SEALWELD.COM

[WWW.SEALWELD.COM](http://WWW.SEALWELD.COM)