

VALVE LUBE SEALANT SPECIFICATION SHEET

80

SCOPE

Valve lube sealant specifications.

ORDERING OPTIONS

Val-Tex Part Number: 80 stick in B, C, D, G, J, K and V

80-S bulk in P packs, 12 oz crtg, 10 lb. can, 40 lb. pail, 120 lb. drum, and 440 lb. drum

REQUIREMENTS**General**

This biodegradable lube sealant is suitable as a multi-purpose lube sealant being resistant to mineral oils, light hydrocarbons, LPG's and all aromatics. It is water resistant. Intermingling of Val-Tex 80 and other lubricants or sealants will not have any adverse affect.

Physical Characteristics**Worked Penetration at 77° F - ASTM D 217**

Bulk: 205 typical

Stick: 86 typical

Dropping Point - ASTM D-566

Bulk: over 500° F typical

Stick: over 500° F typical

National Lubricating Grease Institute Consistency Number

Bulk: 4 typical

Stick: greater than 6 typical

Temperature Range for Proper Lubrication

Bulk: -20° F to +500° F typical

Stick: -20° F to +500° F typical

Color - Amber

REFERENCE STANDARDS AND SPECIFICATIONS

ASTM D 217 Cone Penetration of Lubricating Grease

ASTM D 566-64 Dropping Point of Lubricating Grease

**BIODEGRADABLE VALVE FLUSH
AND VALVE LUBE SEALANTS**

EMAIL SALES.VAL-TEX@CMCMATERIALS.COM