

VALVE LUBE SEALANT SPECIFICATION SHEET

85

SCOPE

Valve lube sealant specifications.

ORDERING OPTIONS

Val-Tex Part Number: 85 stick in B, C, D, G, J, K and V

85-S bulk in P packs, 12 oz crtg, 10 lb. can, 40 lb. pail, 120 lb. drum, and 440 lb. drum

REQUIREMENTS**General**

This biodegradable lube sealant is resistant to mineral oils, light hydrocarbons, LPG's and most aromatics. It's heavy viscosity makes it an excellent performer where there are high differential pressures across the valve. It is water-resistant. Intermingling of Val-Tex No. 85 and other lubricants or sealants will not have any adverse affect. Please consult the factory with any specific questions.

Physical Characteristics**Worked Penetration at 77° F - ASTM D 217**

Bulk: 174 typical

Stick: 62 typical

Dropping Point - ASTM D-566

Bulk: over 500° F typical

Stick: over 50° F typical

National Lubricating Grease Institute Consistency Number

Bulk: 3 to 4 typical

Stick: greater than 6 typical

Temperature Range for Proper Lubrication

Bulk: -20° F to +500° F typical

Stick: -20° F to +500° F typical

Color - Amber

REFERENCE STANDARDS AND SPECIFICATIONS

ASTM D 217 Cone Penetration of Lubricating Grease

ASTM D 566-64 Dropping Point of Lubricating Grease

**BIODEGRADABLE VALVE FLUSH
AND VALVE LUBE SEALANTS**

EMAIL SALES.VAL-TEX@CMCMATERIALS.COM