LE Liquid Eliminator

WELKER

The Welker LE Liquid Eliminator series helps protect sensitive equipment from damage and contamination by removing free liquids from natural gas sample streams. Install the LE as a standalone unit or as part of a conditioning system upstream of your analyzer.

Features

- Integrated liquid and sediment filtration
- Liquid-eliminating chamber
- Self-draining design
- Mounting bracket
- Threaded housing cap (LE-5)

Benefits

- Prevent free liquids and particulates from reaching the analyzer
- Quick and easy installation
- Quick and easy maintenance (LE-5)

SPECIFICATIONS


LE LIQUID ELIMINATORS



LE-2 4 lb | 3.5" x 3" x 3"



LE-3 2.5 lb | 3" x 2.25" x 2.625"



LE-5 3.5 lb | 2.75" x 3.25" x 3.375"

LE-2	LE-2HP	LE-3	LE-5

Materials of Construction	304 Stainless Ste	304 Stainless Steel, 316/316L Stainless Steel, Copolymer Filter Element, Teflon®, Viton®				
Connections		1⁄8" FNPT				
Features		CE Compliance				
_		CE Compliance				
		Threaded Housing Cap				
Operating Pressure	1440 psig @ -20 °F to 120 °F	2160 psig @ -20 °F to 120 °F	1440 psig @ -20 °F to 120 °F			
		3600 psig @ -20 °F to 120 °F		2 160 psig @ -20 °F to 300 °F		
Industry Standards	GPA 2166, API 14.1, ASTM D5287, ISO 10715					
-	1440 psig @ -20 °F to 120 °F	3600 psig @ -20 °F to 120 °F		Mounting Bracket Threaded Housing Cap 2160 psig @ -20 °F to 30		

Weight and/or dimensions are approximate. Specifications subject to change without notice.



 13839 WEST BELLFORT STREET
 SUGAR LAND, TEXAS 77498
 281.491.2331
 sales@welker.com
 WELKER.COM

 ©2020 Welker, Inc., All Rights Reserved.
 Welker', W Welker', W logo, WelkerScope', Welker Jet', and OdorEyes' are registered trademarks owned by Welker, Inc.