

C1200

The model **C1200** Hydraulic Squeeze Off Tool is designed to squeeze 8" to 12" MDPE and HDPE pipe safely and effectively.

The **C1200** features 8-sided, positive locking, indexable gauge plates, aircraft grade aluminum squeeze bars, chrome plated steel side shafts and a 10,000 PSI hydraulic system with quick connect fittings. This CNC machined tool contains no welded parts and exerts 150 tons of squeezing force.

The unique lock-in / swing-out bottom bar design allows for quick and easy access to the pipe, even in confined spaces, and the lock down bolts ensure that a squeeze is maintained even if the hydraulics are disconnected. The **C1200** also incorporates an efficient dog bone design on the jaws to obtain maximum flow control, while requiring minimal force to squeeze the pipe.

The **C1200** also includes a standard grounding spike, and custom gauge plates are available upon request.



C1200-25



Air/Hydraulic pump kit, foot operated c/w controlled release valve, pressure gauge and 20' hoses.

For model C1200-A2 & C36S-A1

For **8"** to **12"** PE & HDPE Pipe
525lbs / Height 37" to 51" / Width 34"
Pump Required: Model C1200-25
ASTM Approved

Standard Gauge Plate Settings
8" (SDR 9, 11, 11.5, 13.5)
10" (SDR 11, 11.5, 13.5, 15.5)
12" (SDR 9, 11, 11.5, 13.5, 15.5)