

# C100



The Model **C100** Manual Squeeze Off Tool is designed to squeeze 1/2" to 2" PE pipe safely and effectively.

The **C100** features 6-sided, positive locking, indexable gauge plates, aircraft grade aluminum squeeze bars, chrome plated steel sideshafts and a coated feed screw, reducing corrosion and friction. This tool can be operated with the detachable

torque bar or with a ratchet on the integral hex at the top of the feed screw. The unique swing-out / lock-in bottom bar design allows for quick and easy access to the pipe even in confined spaces, and the detachable stabilizing bar provides added stability during the squeeze process.

The **C100** also includes a static grounding spike, and custom gauge plates are available upon request.

## Standard Gauge Plate Settings

- 1/2" CTS (SDR 7)
- 3/4" IPS (SDR 11)
- 1" CTS (SDR 11, 11.5)
- 1" IPS (SDR 11)
- 1-1/4" IPS (SDR 10)
- 1-1/2" IPS (SDR 11)
- 2" IPS (SDR 11)



Contact your CR Wall Representative or call 519-624-9293 for more information

www.crwall.com | 519-624-9293  
customerservice@crwall.com

For **1/2"** to **2"** PE Pipe  
**9.5lbs / Height 12" / Width 6.5"**

ASTM Approved