


# Bolt Type Medium Pressure Test Plug

## Simple & Reliable Hydrostatic Testing without Wall Damage

Medium Pressure, ported test plugs designed for simple, reliable hydrostatic testing of pipe and tubing, without tube wall damage associated with other test plugs.



### Test Pressure

Up to 250 psi (17 Bar) - *higher pressures available upon request*

### Size Range

1/4" to 10 1/2" (6.4mm - 266.7mm) Pipe and Tube I.D. - *larger sizes available upon request*

### Standard Materials

Plated carbon steel with Neoprene seals

### Features & Benefits

- Heavy-Duty Construction – corrosion resistant plated carbon steel with neoprene seal elements
- Versatile – wide range of sizes
- Brass Anti-Gall Washer & thread lubricant – protects threads and facilitates test plug installation and removal
- Long Wearing Full Disk Seals – extends plug life
- Easy to Maintain – replacement seals available

### Available Options

- Construction – 300 Series Stainless steel with Silicone or Viton® seals
- High Pressure Pipe Caps – for use in either ported or solid configurations

### Additional Information

- Contact Customer Service for all non-metallic applications
- Not suitable for Gas Pressure Tests
- [DC2600 - Operating Procedures For Bolt Type Test Plugs](#)
- [DC8048 - Bolt Type Test Plug - Technical Specifications](#)

Viton® is a registered trademark of DuPont Dow Elastomers

**North, Central & South America EST Group** 2701 Township Line Road Hatfield, PA 19440-1770 USA | +1.215.721.1100 +1.800.355.7044 | est-info@curtisswright.com

**Europe / Middle East / Africa EST Group B.V.** Hoorn 312a 2404 HL Alphen aan den Rijn The Netherlands | +31.172.418841 | est-emea@curtisswright.com

**China** +86.400.636.5077 | est-china@curtisswright.cn | **Singapore** +65.3158.5052 | est-asia@curtisswright.com