

VALVE LUBE SEALANT SPECIFICATION SHEET

75

SCOPE

Valve lube sealant specifications.

ORDERING OPTIONS

Val-Tex Part Number: 75 stick in B, C, D, G, J, K and V

75-S bulk in lube P packs, 12 oz crtg, 10 lb. can, 40 lb. pail, 120 lb. drum, and 440 lb. drum

REQUIREMENTS**General**

This biodegradable lube sealant was developed for valves used in high temperature systems carrying hydrocarbons in the range from heavy crude oils up to and including the aromatics. Contains moly-disulfide to reduce valve operating torque. Intermingling of Val-Tex 75 and other lubricants will not have any adverse effects.

Physical Characteristics**Worked Penetration at 77° F - ASTM D 217**

Bulk: 198 typical
Stick: 88 typical
SS Bulk: 303 typical

Dropping Point - ASTM D-566

Bulk: over 500° F typical
Stick: over 500° F typical
SS Bulk: over 500° F typical

National Lubricating Grease Institute Consistency Number

Bulk: 4 typical
Stick: 6 typical
SS Bulk: 1 to 2 typical

Temperature Range for Proper Lubrication

Bulk: -20° F to +750° F typical
Stick: -20° F to +750° F typical
SS Bulk: -20° F to +750° F Typical

Color - Black

REFERENCE STANDARDS AND SPECIFICATIONS

ASTM D 217 Cone Penetration of Lubricating Grease
ASTM D 566-64 Dropping Point of Lubricating Grease

**BIODEGRADABLE VALVE FLUSH
AND VALVE LUBE SEALANTS**

EMAIL SALES.VAL-TEX@CMCMATERIALS.COM